



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **04075368 A**(43) Date of publication of application: **10.03.92**

(51) Int. Cl. **H01L 25/04**
H01L 23/36
H01L 25/07
H01L 25/18

(21) Application number: **02189984**(71) Applicant: **HONDA MOTOR CO LTD**(22) Date of filing: **17.07.90**(72) Inventor: **KATOU NARITAKA**(54) **SEMICONDUCTOR DEVICE**

(57) Abstract:

PURPOSE: To improve radiation performance and protect from environment by providing a pair of metal bases, an insulation layer formed on each side opposite to the metal bases, a electrode wiring formed on each insulation layer, and semiconductor devices where electrodes are laid out on the opposite side of each electrode wiring.

CONSTITUTION: Transistors Q_1 and Q_4 are turned on by a control signal transmitted from a gate control circuit, which forces motor drive current to flow in the order of the transistor Q_1 , a motor M, and the transistor Q_4 . On the other hand, transistors Q_2 and Q_3 are turned on, which forces motor drive current to flow in the order of the transistor Q_2 , the motor M, and the transistor Q_3 . In the mean time, the transistors Q_1 , Q_2 , Q_3 , and Q_4 are heated up. The heat is mainly transmitted to a first metal base 1 by way of drain current 4a, a drain electrode wiring 3, and an insulation layer 2. At the same time, the heat is transmitted to a second metal base by way of a source electrode 4b or a source electrode 4c and a source electrode wiring 7 or a gate electrode wiring 8, and an insulation layer 6 and further to the connected first

metal base 1. The heat thus transmitted is emitted into the air from radiation fins 1a.

COPYRIGHT: (C)1992,JPO&Japio

